



Notes:

- The laser device is not designed for reverse operation
- Window thickness is 0.25 ± 0.05
- Distance between emission point and window: < 0.35
- Power up laser only after package is connecte to a suitable heatsink
- The only acceptable surface for heat transfer is the bottom of the base plate

Material:		nanoplus Nanosystems and Technologies GmbH Oberer Kirschberg 4, 97218 Gerbrunn, Germany © copyright nanoplus GmbH 2021, all rights reserved nanoplus GmbH reserves the right to modify specifications at any time without notice and is not liable for errors.		Description:	
Finish:		Unless Otherwise Stated: ISO 2768 fK Surface Finish: All Dimensions: mm		Drawing Scale:	
Drawing Scale:		10:1		Approx Weight:	
Approx Weight:		g		Drawing Produced In Accordance With: BS8888	
Projection Method:		THIRD ANGLE		Sheet Size:	
Projection Method:		THIRD ANGLE		A3	
Legal Owner:		Nanosystems and Technologies GmbH		Part Name:	
Legal Owner:		nanoplus		TO5.6 mit Laser und Kappe	
Checked/Approved by:		WZ		Checked/Approved Date:	
Checked/Approved by:		WZ		24.11.2023	
Drawn by:		WZ		Drawn Date:	
Drawn by:		WZ		24.11.2023	
Drawing Number:		Sheet:		Revision:	